



MR120
12" – 800 WATT MAX POWER

MR100
10" – 600 WATT MAX POWER

MARINE 4-OHM SUBWOOFER
Featuring Polypropylene Cone and KAPTON Voice Coil



MR105
10" – 1000 WATT MAX POWER

MARINE 4-OHM SUBWOOFER
Featuring Polypropylene Cone and Aluminum Voice Coil



MR752C
7.5" – 400 WATT MAX POWER

MR652C
6.5" – 350 WATT MAX POWER

2-WAY MARINE LOUDSPEAKER
Featuring Poly Injection Cone and Aluminum Voice Coil

SPECIFICATIONS	POWER HANDLING (PEAK)	IMPEDANCE	FREQUENCY RESPONSE	SPL 1 WATT/ 1 METER	CONE MATERIAL	VOICE COIL	TWEETER(S)	MOUNTING DEPTH
MR752C	400W	4 OHMS	40Hz–20kHz	90dB	POLY INJECTION	1-1/2" ALUMINUM	1" MYLAR DOME	2-3/4"
MR652C	350W	4 OHMS	60Hz–20kHz	92dB	POLY INJECTION	1-1/2" ALUMINUM	1" MYLAR DOME	2-7/16"
MR65G3	250W	4 OHMS	60Hz–20kHz	92dB	PP CARBON	1" ASV	1" MYLAR DOME	2-3/4"

MARINE SUBWOOFERS AND LOUDSPEAKERS



WHITE



CHROME



BLACK



MR65G3

6.5" – 250 WATT MAX POWER

2-WAY MARINE LOUDSPEAKER

Featuring Interchangable Grill Combinations – White, Chrome and Black

WHITE | CHROME | BLACK

BOSS® marine

SPECIFICATIONS	POWER HANDLING (PEAK)	POWER HANDLING (RMS)	IMPEDANCE	FREQUENCY RESPONSE	SPL 1 WATT/ 1 METER	CONE MATERIAL	VOICE COIL	MOUNTING DEPTH
MR120	800W	400W	4 OHMS	25Hz–2kHz	94dB	POLYPROPYLENE	2-1/2"	5-3/4"
MR100	600W	300W	4 OHMS	30Hz–2.5kHz	94dB	POLYPROPYLENE	2"	4-5/8"
MR105	1000W	500W	4 OHMS	25Hz–2kHz	96dB	POLYPROPYLENE	2"	4-1/8"

	BOX TYPE	SEALED BOX (SM)	SEALED BOX (LG)	PORTED BOX (SM)	PORT (DIA)	PORT (LENGTH)	TUNING (FREQ)	PORTED BOX (LG)	PORT (DIA)	PORT (LENGTH)	TUNING (FREQ)
MR120	SEALED or PORTED	0.4 (cu. ft.)	1.2 (cu. ft.)	13/16"	3"	10"	45.0	1"	3"	7-1/2"	42.0
MR100	SEALED or PORTED	0.5 (cu. ft.)	1.5 (cu. ft.)	1-1/2"	4"	8"	45.0	2"	4"	7-1/2"	40.0
MR105	SEALED or PORTED	0.3 (cu. ft.)	0.7 (cu. ft.)	13/16"	3"	10"	45.0	1"	3"	7-1/2"	42.0